

209 SAWMILL ROAD • REEDSVILLE, PA 17084 • 717.667.9373

Premium Engineered Flooring Specifications

Peachey® Premium Engineered Hardwood Flooring is designed to withstand demanding conditions such as on concrete, over radiant heat, below grade and very wide plank installations while maintaining excellent structural stability

Standard structural warranty applies if installed and maintained according to NWFA guidelines

Engineered flooring can be made in any domestic species that we carry and is available in

1/2", 5/8"& 3/4" thickness

Widths are available up to 16" and lengths up to 12 feet

Typically, Peachey[®] Premium Engineered Hardwood Flooring can be professionally sanded and refinished by an NWFA certified specialist the same number of times as a solid floor

All engineered flooring consists of a CARB II compliant multiply Baltic Birch plywood with waterproof glue between the plies and between the substrate & wear layer

Milling tolerances are to NWFA specifications of +-.005" or less

Plywood & resulting wear layer tolerance is +-.3MM

- 1/2" 7 ply Baltic Birch plywood with 3MM wear layer
- 5/8" 9 ply Baltic Birch plywood with 4MM wear layer
- 3/4" 11 ply Baltic Birch plywood with 4MM wear layer
- 3/4" optional 9 ply Baltic Birch plywood with 6MM wear layer